



Speclight Co., Ltd.

973 President Tower, 11th Floor, Room 11G, 11H,
Ploenchit Rd., Lumpini, Pathumwan Bangkok 10330

Tel : 0-2117-9408 Fax : 0-2903-0080 #7272

E-mail : contact.speclight@gmail.com, project@speclight.co.th

www.LEDLIGHTING.in.th



- Five-stage zinc phosphate pretreatment for rust resistance.
 - Finished with white polyester powder by two-stage electrostatic method.
 - Rotary-locked type starter holder (TIS.344-1987 Standard)
 - Heavy duty spring-locked type lamp holder (TIS.344-1987 Standard).
- Other lamp holder types are available.

WR = Rotary-locked type lamp holder (G13)

WP = Waterproof type lamp holder

- Cable THW 1.0 sq.mm. 70°C (TIS.11-1988 Standard).
- Suitable for general purpose with high efficiency requirement

WATT	DIMENSION (mm.)		
	L	W	H
1 x T8 18w.	636	64	112
2 x T8 18w.	636	124	112
1 x T8 36w.	1245	64	112
2 x T8 36w.	1245	124	112



Speclight provides professional lighting design services and lighting consulting to architects, interior designers, project managers, landscape architects and property owners from small to large projects. Services vary from conceptual lighting design through to opening day and beyond. Projects may range from a few hours of consulting to large scale projects with complete documentation followed with on site services.